

FEATURES	SLEEKLINE	GLASS
Irregular Glazing Shapes	Irregular shapes are easy and affordable	Higher expense and longer lead times
Field Modification	Can be easily modified in the field	Cannot be field cut requires exact measuring, edge work, pattern changes and heat strengthening
Safety	Will not break or shatter under extreme loading conditions	Laminated glass can break and has the potential of falling debris, requiring immediate replacement
Impact Resistance	250 times the impact resistance of standard glass	Is not impact resistant
Available Colors	Over 100 standard colors available	Colors are custom
1/4" Panel Weight	1 PSF	3.5 - 10 PSF
Panel Length	Continuous panel lengths up to 40 feet	Length limitations create the need for more stand-offs and causes deflection issues
Deflection	Can deflect more than 8 times the amount of glass without failure	Small deflection limits require more structure and expense
Sealants	All sealants are dry seal sand do not require maintenance	Requires butt-joints, installation of sealants are weather permitting, expensive and take time to cure
Organic Designs	Panels can be cut and formed to desired configuration without the cost of specialty customization	Expensive to customize
Cost of Installation	Lighter structure and larger panels significantly reduce installation time	Larger field crew and power equipment needed, requires more time to install
Project Cost	Save on shipping, product, installations, maintenance and modifications	Higher cost of shipping, product, installations, maintenance and modifications